



# DIN 55473 Desiccants

DDC-Din desiccants are suitable for use in industrial and military environments. This all-natural product is made from dried clay. DDC-DIN features a dust-proof packaging.

[View online](#) →

## 01 Applications

DDC-DIN products can be used in a wide variety of environments. We offer solutions for e.g.:

- Industrial solutions
- Packaging for machines
- Packaging for military products and tools (meets applicable quality standards)
- Suitable for use inside transport crates
- Transport of military and industrial products
- Leather products
- Electronic equipment
- Airfreight

## 02 Technical information

The use of DDC-DIN desiccants is advised when reliable high-grade protection against moisture is needed. A desiccant for industrial environments in accordance with the DIN 55 473 and military standards MIL-D-3464E.

This is particularly important for protective packaging materials that must be durable and capable of withstanding different climate conditions, as is the case with classical export packagings.

**Price on request**

DU*	Weight	Product number	Dimensions	Qty. per box
1/6	6 g	CBB1/6	70 x 32 x 8 mm	1.500
1/3	12 g	CBB1/3	80 x 65 x 8 mm	800
1/2	18 g	CBB1/2	85 x 75 x 9 mm	600
1	36 g	CBB001	90 x 75 x 10 mm	400
2	75 g	CBB002	125 x 100 x 13 mm	240
4	150 g	CBB004	155 x 100 x 16 mm	120
8	285 g	CBB008	180 x 120 x 20 mm	70
16	590 g	CBB016	210 x 170 x 25 mm	35
32	1.140 g	CBB032	280 x 170 x 40 mm	18

\*DU: refers to its drying capability, not in volume, and is the amount of desiccant which will absorb at least 6 grams of water vapor at 40% RH at 25°C(77°F).

